



Trimboards | Sidings | Mouldings

30-YEAR LIMITED WARRANTY

A 30-year limited warranty is provided on all Bodyguard[®] products against termite attack, rot or fungal decay.

INDOOR AND EXTERIOR USE

Bodyguard[®] is safe for indoor use, as well as exterior use (above ground only).

DURABLE

Bodyguard[®] is treated under pressure, achieving total active penetration protection. The addition of waxes and resins into the formulation enhances its water protection properties. The active ingredients used in the treatment process are insoluble in water and will not be removed through leaching.

TERMITE RESISTANT

One of the active protective ingredients in Bodyguard[®] is permethrin, a food-crop protection product that is proven effective against all known species of termite

PAINT-READY FINISH

The machined finish of Bodyguard[®] is enhanced by a two-coat primer system, with a performance warranty. Finish your Bodyguard[®] surface with a good-quality acrylic paint system to the manufacturer's specification

TREE-FARMED FORESTS

All Bodyguard[®] products are sourced from well-managed plantation forests, sustainably grown in New Zealand.

GREEN BUILDING CREDITS

Bodyguard qualifies for credit points under the following schemes:

- LEED for Homes
- NAHB Model Green Home Building Guidelines
- GreenPoint Rated (California only)

FSC CERTIFIED

By buying products with an FSC label you are helping to promote responsible forest management worldwide. Ask for our supply availability of FSC certified products (SGS-COC-003178 / SCS-COC-00538 / SGS-COC-2410 / SGS-COC-004276).

ENVIRONMENTALLY FRIENDLY

Bodyguard[®] preservative system is based on organic biocides and is registered in the United States of America by the EPA.

SAFE TO HANDLE

As Bodyguard[®] is real wood and contains no hazardous additives it's safe to work with; just follow normal work-place safety practises.

EASE OF USE

No special tools, cutting equipment or fixing methods are required.

DEFECT FREE

Bodyguard[®] is a natural wood product manufactured from kiln-dried timber. All defects are removed prior to finger-jointing, then surfaced for a paint-ready finish.

NON-CORROSIVE

As the organic treatment does not contain any corrosive heavy metals it will not cause corrosion to nails and other fastening systems. Durable fasteners are recommended as good building practise for exterior applications.

CALIFORNIAN FIRE APPROVAL

Bodyguard have had profiles successfully tested by Western Fire Center Inc., to Californian State Fire Marshall Regulations.

Sidings: Tested in accordance with Californian State Fire Marshall Regulation 12.7A-1. This approval is for horizontal applications only and requires installation over OSB with a minimum thickness of 7/16".

Under Eaves: Tested in accordance with California State Fire Marshall Regulation 12.7A-3. This approval is for T&G beaded product (#801 & #802) and must be mounted over a minimum of 1/2" exterior grade gypsum board.

Listed on the Building Materials Listing Program with the California State Fire Marshall.

www.osfm.fire.ca.gov/pdf/fireengineering/bml/wuiproducts.pdf